



Face Mount Hangers - Load Capacity For Screwed Connection							
Model #	ga	Joist Size	Header Screws	Screw Size	Joist Screws	Screw Size	Max Load-lbs
JH24	18	2x4	4	#10x1.5	4	#10x1.5	438
JH24	18	2x4	4	#10x2.5	4	#10x2.5	630
JH26	18	2x6	6	#10x1.5	4	#10x1.5	658
JH26	18	2x6	6	#10x2.5	4	#10x2.5	990
JH26	16	2x6	6	#10x1.5	4	#10x1.5	663
JH26	16	2x6	6	#10x2.5	4	#10x2.5	990
JH26-2	16	2-2x6	6	#10x1.5	4	#10x1.5	663
JH26-2	16	2-2x6	6	#10x2.5	4	#10x2.5	1086
JH28	18	2x8	10	#10x1.5	6	#10x1.5	1096
JH28	18	2x8	10	#10x2.5	6	#10x2.5	1305
JH28	16	2x8	10	#10x1.5	6	#10x1.5	1104
JH28	16	2x8	10	#10x2.5	6	#10x2.5	1305
JH28-2	16	2-2x8	10	#10x1.5	6	#10x1.5	1104
JH28-2	16	2-2x8	10	#10x2.5	6	#10x2.5	1753
JH210-12	16	2x10	12	#10x1.5	8	#10x1.5	1325
JH210-12	16	2x10	12	#10x2.5	8	#10x2.5	1665
JH210-12	16	2x12	12	#10x1.5	8	#10x1.5	1325
JH210-12	16	2x12	12	#10x2.5	8	#10x2.5	1875
JH210-2	16	2-2x10	12	#10x1.5	8	#10x1.5	1325
JH210-2	16	2-2x10	12	#10x2.5	8	#10x2.5	2172
JH212-2	16	2-2x12	16	#10x1.5	8	#10x1.5	1767
JH212-2	16	2-2x12	16	#10x2.5	8	#10x2.5	2666

1. Load values based on Douglas Fir-Larch
2. All specified fasteners must be used.
3. All screws are stainless steel.
4. Minimum header size 4x.
5. Loads based on dry condition.
6. Basis of design, NDS 2015.



Face Mount Hangers - Load Capacity For Screwed Connection							
Model #	ga	Joist Size	Header Screws	Screw Size	Joist Screws	Screw Size	Max Load-lbs
JH44	16	4x6	4	#10x1.5	2	#10x1.5	442
JH44	16	4x6	4	#10x2.5	2	#10x2.5	667
JH46-8	16	4x6	8	#10x1.5	4	#10x1.5	883
JH46-8	16	4x6	8	#10x2.5	4	#10x2.5	1333
JH46-8	16	4x8	8	#10x1.5	4	#10x1.5	883
JH46-8	16	4x8	8	#10x2.5	4	#10x2.5	1333
JH410	16	4x10	14	#10x1.5	8	#10x1.5	1546
JH410	16	4x10	14	#10x2.5	8	#10x2.5	2419
JH412	16	4x12	16	#10x1.5	8	#10x1.5	1767
JH412	16	4x12	16	#10x2.5	8	#10x2.5	2666
JH26-2INV	16	2-2x6	6	#10x1.5	4	#10x1.5	663
JH26-2INV	16	2-2x6	6	#10x2.5	4	#10x2.5	1086
JH28-2INV	16	2-2x8	10	#10x1.5	6	#10x1.5	1104
JH28-2INV	16	2-2x8	10	#10x2.5	6	#10x2.5	1753
JH210-2INV	16	2-2x10	12	#10x1.5	8	#10x2.5	1325
JH210-2INV	16	2-2x10	12	#10x2.5	8	#10x2.5	2172
JH44INV	16	4x6	4	#10x1.5	2	#10x1.5	442
JH44INV	16	4x6	4	#10x2.5	2	#10x2.5	667
JH46-8INV	16	4x6	8	#10x1.5	4	#10x1.5	883
JH46-8INV	16	4x6	8	#10x2.5	4	#10x2.5	1333
JH46-8INV	16	4x8	8	#10x1.5	4	#10x1.5	883
JH46-8INV	16	4x8	8	#10x2.5	4	#10x2.5	1333
JH410INV	16	4x10	14	#10x1.5	8	#10x1.5	1546
JH410INV	16	4x10	14	#10x2.5	8	#10x2.5	2419

1. Load values based on Douglas Fir-Larch
2. All specified fasteners must be used.
3. All screws are stainless steel.
4. Minimum header size 4x.
5. Loads based on dry condition.
6. Basis of design, NDS 2015.



Face Mount Hangers - Load Capacity For Screwed Connection							
Model #	ga	Joist Size	Header Screws	Screw Size	Joist Screws	Screw Size	Max Load-lbs
JH412INV	16	4x12	16	#10x1.5	8	#10x1.5	1767
JH412INV	16	4x12	16	#10x2.5	8	#10x2.5	2666
BH66	14	6x6	10	#10x1.5	4	#10x1.5	1120
BH66	14	6x6	10	#10x2.5	4	#10x2.5	1614
BH68	14	6x8	10	#10x1.5	6	#10x1.5	1123
BH68	14	6x8	10	#10x2.5	6	#10x2.5	1787
BH610	14	6x10	18	#10x1.5	8	#10x1.5	2022
BH610	14	6x10	18	#10x2.5	8	#10x2.5	2974
BH612	14	6x12	22	#10x1.5	8	#10x1.5	2471
BH612	14	6x12	22	#10x2.5	8	#10x2.5	3482
BH66INV	14	6x6	10	#10x1.5	4	#10x1.5	1120
BH66INV	14	6x6	10	#10x2.5	4	#10x2.5	1614
BH68INV	14	6x8	10	#10x1.5	6	#10x1.5	1123
BH68INV	14	6x8	10	#10x2.5	6	#10x2.5	1787
BH610INV	14	6x10	18	#10x1.5	8	#10x1.5	2022
BH610INV	14	6x10	18	#10x2.5	8	#10x2.5	2974
BH612INV	14	6x12	22	#10x1.5	8	#10x1.5	2471
BH612INV	14	6x12	22	#10x2.5	8	#10x2.5	3482

1. Load values based on Douglas Fir-Larch
2. All specified fasteners must be used.
3. All screws are stainless steel.
4. Minimum header size 4x.
5. Loads based on dry condition.
6. Basis of design, NDS 2015.