



Face Mount Hangers - Load Capacity For <i>Nailed Connection</i>							
Model #	ga	Joist Size	Header Nailing	Nail Size	Joist Nailing	Nail Size	Max Load-lbs
JH24	18	2x4	4	10dx1.5	4	10dx1.5	453
JH24	18	2x4	4	10dx3	4	10dx3	630
JH24	18	2x4	4	16dx3.5	4	16dx3.5	630
JH26	18	2x6	6	10dx1.5	4	10dx1.5	679
JH26	18	2x6	6	10dx3	4	10dx3	990
JH26	18	2x6	6	16dx3.5	4	16dx3.5	990
JH26	16	2x6	6	10dx1.5	4	10dx1.5	685
JH26	16	2x6	6	10dx3	4	10dx3	990
JH26	16	2x6	6	16dx3.5	4	16dx3.5	990
JH26-2	16	2-2x6	6	10dx1.5	4	10dx1.5	685
JH26-2	16	2-2x6	6	10dx3	4	10dx3	1094
JH26-2	16	2-2x6	6	16dx3.5	4	16dx3.5	1304
JH28	18	2x8	10	10dx1.5	6	10dx1.5	1132
JH28	18	2x8	10	10dx3	6	10dx3	1305

1. Load values based on Douglas Fir - Larch.
2. All specified fasteners must be used.
3. All nails are stainless steel common.
4. Minimum header size 4x.
5. Loads based on dry condition.
6. Basis of design. NDS 2015.



Face Mount Hangers - Load Capacity For <i>Nailed Connection</i>							
Model #	ga	Joist Size	Header Nailing	Nail Size	Joist Nailing	Nail Size	Max Load-lbs
JH28	18	2x8	10	16dx3.5	6	16dx3.5	1305
JH28	16	2x8	10	10dx1.5	6	10dx1.5	1142
JH28	16	2x8	10	10dx3	6	10dx3	1305
JH28	16	2x8	10	16dx3.5	6	16dx3.5	1305
JH28-2	16	2-2x8	10	10dx1.5	6	10dx1.5	1142
JH28-2	16	2-2x8	10	10dx3	6	10x3	1758
JH28-2	16	2-2x8	10	16dx3.5	6	16dx3.5	2095
JH210-12	16	2x10	12	10dx1.5	8	10dx1.5	1370
JH210-12	16	2x10	12	10dx3	8	10dx3	1665
JH210-12	16	2x10	12	16dx3.5	8	16dx3.5	1665
JH210-12	16	2x12	12	10dx1.5	8	10dx1.5	1370
JH210-12	16	2x12	12	10dx3	8	10dx3	1875
JH210-12	16	2x12	12	16dx3.5	8	16dx3.5	1875
JH210-2	16	2-2x10	12	10dx1.5	8	10dx1.5	1370
JH210-2	16	2-2x10	12	10dx3	8	10dx3	2188
JH210-2	16	2-2X10	12	16dx3.5	8	16dx3.5	2608

1. Load values based on Douglas Fir - Larch.
2. All specified fasteners must be used.
3. All nails are stainless steel common.
4. Minimum header size 4x.
5. Loads based on dry condition.
6. Basis of design. NDS 2015.



Face Mount Hangers - Load Capacity For <i>Nailed Connection</i>							
Model #	ga	Joist Size	Header Nailing	Nail Size	Joist Nailing	Nail Size	Max Load-lbs
JH212-2	16	2-2x12	16	10dx1.5	8	10dx1.5	1827
JH212-2	16	2-2x12	16	10dx3	8	10dx3	2657
JH212-2	16	2-2x12	16	16dx3.5	8	16dx3.5	3166
JH44	16	4x6	4	10dx1.5	2	10dx1.5	457
JH44	16	4x6	4	10dx3	2	10dx3	664
JH44	16	4x6	4	16dx3.5	2	16dx3.5	791
JH46-8	16	4x6	8	10dx1.5	4	10dx1.5	914
JH46-8	16	4x6	8	10dx3	4	10dx3	1329
JH46-8	16	4x6	8	16dx3.5	4	16dx3.5	1583
JH46-8	16	4x8	8	10dx1.5	4	10dx1.5	914
JH46-8	16	4x8	8	10dx3	4	10dx3	1329
JH46-8	16	4x8	8	16dx3.5	4	16dx3.5	1583
JH410	16	4x10	14	10dx1.5	8	10dx1.5	1599
JH410	16	4x10	14	10dx3	8	10dx3	2423
JH410	16	4x10	14	16dx3.5	8	16dx3.5	2887
JH412	16	4x12	16	10dx1.5	8	10dx1.5	1827

1. Load values based on Douglas Fir - Larch.
2. All specified fasteners must be used.
3. All nails are stainless steel common.
4. Minimum header size 4x.
5. Loads based on dry condition.
6. Basis of design. NDS 2015.



Face Mount Hangers - Load Capacity For <i>Nailed Connection</i>							
Model #	ga	Joist Size	Header Nailing	Nail Size	Joist Nailing	Nail Size	Max Load-lbs
JH412	16	4x12	16	10dx3	8	10dx3	2657
JH412	16	4x12	16	16dx3.5	8	16dx3.5	3166
JH26-2INV	16	2-2x6	6	10dx1.5	4	10dx1.5	685
JH26-2INV	16	2-2x6	6	10dx3	4	10dx3	1094
JH26-2INV	16	2-2x6	6	16dx3.5	4	16dx3.5	1304
JH28-2INV	16	2-2x8	10	10dx1.5	6	10dx1.5	1142
JH28-2INV	16	2-2x8	10	10dx3	6	10dx3	1758
JH28-2INV	16	2-2x8	10	16dx3.5	6	16dx3.5	2095
JH210-2INV	16	2-2x10	12	10dx1.5	8	10dx1.5	1370
JH210-2INV	16	2-2x10	12	10dx3	8	10dx3	2188
JH210-2INV	16	2-2x10	12	16dx3.5	8	16dx3.5	2608
JH44INV	16	4x6	4	10dx1.5	2	10dx1.5	457
JH44INV	16	4x6	4	10dx3	2	10dx3	664
JH44INV	16	4x6	4	16dx3.5	2	16dx3.5	791
JH46-8INV	16	4x6	8	10dx1.5	4	10dx1.5	914
JH46-8INV	16	4x6	8	10dx3	4	10dx3	1329

1. Load values based on Douglas Fir - Larch.
2. All specified fasteners must be used.
3. All nails are stainless steel common.
4. Minimum header size 4x.
5. Loads based on dry condition.
6. Basis of design. NDS 2015.



Face Mount Hangers - Load Capacity For <i>Nailed Connection</i>							
Model #	ga	Joist Size	Header Nailing	Nail Size	Joist Nailing	Nail Size	Max Load-lbs
JH46-8INV	16	4x6	8	16dx3.5	4	16dx3.5	1583
JH46-8INV	16	4x8	8	10dx1.5	4	10dx1.5	914
JH46-8INV	16	4x8	8	10dx3	4	10dx3	1329
JH46-8INV	16	4x8	8	16dx3.5	4	16dx3.5	1583
JH410INV	16	4x10	14	10dx1.5	8	10dx1.5	1599
JH410INV	16	4x10	14	10dx3	8	10dx3	2423
JH410INV	16	4x10	14	16dx3.5	8	16dx3.5	2887
JH412INV	16	4x12	16	10dx1.5	8	10dx1.5	1827
JH412INV	16	4x12	16	10dx3	8	10dx3	2657
JH412INV	16	4x12	16	16dx3.5	8	16dx3.5	3166
BH66	14	6x6	10	10dx1.5	4	10dx5	1160
BH66	14	6x6	10	10dx3	4	10dx3	1598
BH66	14	6x6	10	16dX3.5	4	16dX3.5	1898
BH68	14	6x8	10	10dx1.5	6	10dx1.5	1163
BH68	14	6x8	10	10dx3	6	10dx3	1793
BH68	14	6x8	10	16dx3.5	6	16dx3.5	2129

1. Load values based on Douglas Fir - Larch.
2. All specified fasteners must be used.
3. All nails are stainless steel common.
4. Minimum header size 4x.
5. Loads based on dry condition.
6. Basis of design. NDS 2015.



Face Mount Hangers - Load Capacity For <i>Nailed Connection</i>							
Model #	ga	Joist Size	Header Nailing	Nail Size	Joist Nailing	Nail Size	Max Load-lbs
BH610	14	6x10	18	10dx1.5	8	10dx1.5	2094
BH610	14	6x10	18	10dx3	8	10dx3	2954
BH610	14	6x10	18	16dx3.5	8	16dx3.5	3504
BH612	14	6x12	22	10dx1.5	8	10dx1.5	2559
BH612	14	6x12	22	10dx3	8	10dx3	3437
BH612	14	6x12	22	16dx3.5	8	16dx3.5	4076
BH66INV	14	6x6	10	10dx1.5	4	10dx1.5	1160
BH66INV	14	6x6	10	10dx3	4	10dx3	1598
BH66INV	14	6x6	10	16dx3.5	4	16dx3.5	1898
BH68INV	14	6x8	10	10dx1.5	6	10dx1.5	1163
BH68INV	14	6x8	10	10dx3	6	10dx3	1793
BH68INV	14	6x8	10	16dx3.5	6	16dx3.5	2129
BH610INV	14	6x10	18	10dx1.5	8	10dx1.5	2094
BH610INV	14	6x10	18	10dx3	8	10dx3	2954
BH610INV	14	6x10	18	16dx3.5	8	16dx3.5	3504
BH612INV	14	6x12	22	10dx1.5	8	10dx1.5	2559

1. Load values based on Douglas Fir - Larch.
2. All specified fasteners must be used.
3. All nails are stainless steel common.
4. Minimum header size 4x.
5. Loads based on dry condition.
6. Basis of design. NDS 2015.



Face Mount Hangers - Load Capacity For <i>Nailed Connection</i>							
Model #	ga	Joist Size	Header Nailing	Nail Size	Joist Nailing	Nail Size	Max Load-lbs
BH612INV	14	6x12	22	10dx3	8	10dx3	3437
BH612INV	14	6x12	22	16dx3.5	8	16dx3.5	4076

1. Load values based on Douglas Fir - Larch.
2. All specified fasteners must be used.
3. All nails are stainless steel common.
4. Minimum header size 4x.
5. Loads based on dry condition.
6. Basis of design. NDS 2015.